

Up to 2 systems in parallel connection, gains **double** energy storage and power output



# EOV series

## Solar Energy Storage System

SR-EOV05S-220      SR-EOV15S-220  
 SR-EOV10S-220      SR-EOV20S-220



### Easy to upscale

- Up to 4 batteries in parallel expand to 20.48kWh
- Up to 2 systems in parallel with double storage & output

### User friendly

- Get started quickly and use it instantly
- Min. width of just 13cm, saving space in the home

### Safety

- High quality lithium iron phosphate cells
- Proven Li-ion battery management solutions

### Easy to install

- No matching and commissioning required, ready to install
- Plug-and-play, eliminate the clutter of wires


### Intelligence

- Support Wifi view real-time data through APP
- Large LCD screen with real-time data

### Designed for families


- Support Off-grid/Hybrid/On-Grid output
- Multiple charge and discharge modes available

SR-EOV05S-220




1150\*560\*130mm  
 1 inv 5kW  
 1 Bat 5.12kWh

SR-EOV10S-220




1750\*560\*130mm  
 1 inv 5kW  
 2 Bat 10.24kWh

SR-EOV15S-220



1750\*560\*130mm 650\*560\*130mm  
 1 inv 5kW  
 3 Bat 15.36kWh

SR-EOV20S-220



1750\*560\*130mm 1250\*560\*130mm  
 1 inv 5kW  
 4 Bat 20.48kWh

Inverter Module	SR-EOV05C-220	Can Be Set
<b>Output</b>		
Rated Output Power	5,000W	
Max. Peak Power	10,000VA	
Load Capacity of Motor	4HP	
Wave Form	Pure Sine Wave	
Rated Output Voltage	220Vac (single-phase)	✓
Max. Parallel Capacity	2 units (up to 10kW)	✓
Output Mode	Off-grid/Hybrid/On-grid	✓
<b>Solar Input</b>		
Solar Charge Type	MPPT	
Max. Solar Array Power	5,500W	
Max. Solar Open Circuit Voltage	500Vdc	
<b>Grid / Generator Input</b>		
Input Voltage Range	90~280Vac	
Bypass Overload Current	40A	
<b>Battery Charging</b>		
Max. Solar Charging Current	100A	✓
Max. Grid/Generator Charging Current	60A	✓
<b>General</b>		
Dimension	500*555*130mm	
Battery Module	SR-EOV05B	Can Be Set
Battery Power	5.12kWh	
Rated Voltage	51.2V	
Rated Capacity	100Ah	
Battery Type	LFP	
Cycling Lifespan	6000 (80%DOD,0.5C,25°C)	
Max. Parallel Capacity	4 units (up to 20.48kWh)	✓
Dimension	600*555*130mm	
Standard	UN38.3,MSDS,UL1973, IEC62619, IEC61000 RoHS	