

BADU®Tec

High rate sand filter
Hoë werkverrigting sand filter



The BADU®Tec range of sand filters is manufactured by Speck and has all the features and quality that you as a customer require.

The BADU®Tec range of sand filter has a seamless, one piece molded polyethylene tank. Fitted complete with our smooth operating top mounted multiport valve for easy selection of standard operating features.

The BADU®Tec range of sand filters is strong, reliable and simple to operate. They feature non-corrosive high flow ABS internal components and an automatic internal air relief system.

The BADU®Tec range of sand filters is fully factory tested and under normal operating conditions carry a 12 month ex-factory warranty on the tank, the Multiport valve and internal parts from date of purchase.

The **BADU®Tec** range of filters is manufactured by **Speck Pumps** and has all the features and quality that you as a customer require.

Die reeks **BADU®Tec** filters word deur **Speck Pumps** vervaardig en het al die eienskappe sowel as die gehalte waarna u as 'n kliënt soek.

Die BADU®Tec sandfilters word deur Speck vervaardig en het al die eienskappe sowel as die gehalte waarna u as kliënt soek.

Die reeks BADU®Tec sandfilters het 'n soomlose, eenstuk gevormde polieten-tenk. Dit is volledig toegerus met ons kant-gemonteerde, gladde werking, meerdoelige kontroleklep wat dit maklik maak om die verlengde verstelling te kies.

Die reeks BADU®Tec sandfilters is sterk, betroubaar en eenvoudig om te gebruik. Dit word van roesbestande, hoëvloei ABS interne komponente vervaardig en het 'n outomatiese, ingeboude luguitlaatstelsel.

Die reeks BADU®Tec sandfilters is volledig fabriek-getoets en het 'n 12 maande fabriekswaarborg op die tenk, die meerdoelige kontroleklep en interne komponente onder normale werktoestande vanaf datum van aankoop.

Code / Kode	Description / Beskrywing
702.0000.001	BADU®Tec 1 Filter

Technical data / Tegniese data	BADU®TEC 1
Weight excl. sand in kg	9.93
Filter sand in kg	40
Filter area in m ²	0.17
Flow rate in m ³ /h at 80kPa	6.0
Average pool size in ℓ	35 000

Turnover rate in liters / Omkeertempo in liter	
4 hour turnover rate in 1	23350
6 hour turnover rate in 1	35000
8 hour turnover rate in 1	46670