

BADU®Koi Filter

High rate sand filter

Hoë werkverrigting sand filter



BADU®Koi Filter

The **BADU®Koi** sand filter has a new unique quick release lid for easy manual back washing and maintenance, together with the smooth operating side mounted multiport valve. This makes the filter user friendly and simple to operate.

The **BADU®Koi** sand filter has a Roto-moulded one piece polyethylene tank, for strength and leakage prevention.

The **BADU®Koi** sand filter has an automatic air relief system therefore there is no pressure build up inside the tank. All the materials used for the manufacture of the BADU®Koi sand filters are non corrosive and UV resistant as well as being non-toxic, for long life satisfaction in filter operation.

The **BADU®Koi** sand filter features twelve angled free flow internal collector arms offering improved water filtration. Nature's answer to healthy fish.

The **BADU®Koi** sand filter is fully factory tested and under normal operating conditions carries a 18 month ex-factory warranty from date of purchase on the tank, 60 months on the Multiport valve, lid clamp ring and internal parts.

The **BADU®Koi** range of sand filters is manufactured by **Speck Pumps** and has all the special features and quality that you as a koi enthusiast would require. This allows you the satisfaction and enjoyment you deserve from your koi pond or water feature.

Die reeks **BADU®Koi**-sandfilters word deur **Speck Pumps** vervaardig en het al die spesiale eienskappe sowel as die gehalte waarna u as 'n koi-liefhebber soek om te verseker dat u koi dam of waterelement u net genot verskaf.

Die **BADU®Koi**-sandfilter het 'n unieke nuwe deksel wat maklik oopmaak om hand-terugspoeling en onderhoud te vergemaklik, asook 'n gladde werking, kant-gemonteerde meerdoelige kontroleklep om kliënte 'n gebruikersvriendelike filter te bied wat maklik is om te gebruik.

Die **BADU®Koi**-filter het 'n roto gevormde, eenstuk poli-etileen-tenk vir ekstra versterking en om lekkasies te voorkom.

Die **BADU®Koi**-sandfilter het 'n outomatiese luguitlaatstelsel, dus bou daar nie druk binne-in die tenk op nie. Al die komponente wat vir die vervaardiging van die BADU®Koi-sandfilters gebruik word, is roes- en UV-bestand en nie-toksies om langdurige, bevredigende werking te verseker.

Een van die kenmerke van die **BADU®Koi**-sandfilter is die twaalf hoekige, vryvloei interne opvangarms om waterfiltrering te verbeter – die natuur se manier om gesonde visse te verseker.

Die **BADU®Koi** is volledig fabriek-getoets en het 'n 18 maande fabriekswaarborg op die tenk, 60 maande op die meerdoelige kontroleklep en interne komponente onder normale werktoestande vanaf datum van aankoop.

Code / Kode	Description / Beskrywing
701.5000.001	BADU®Koi Filter 1 with standard valve
701.5000.002	BADU®Koi Filter 2 with standard valve
701.5000.003	BADU®Koi Filter 3 with standard valve
701.5000.004	BADU®Koi Filter 4 with standard valve

Technical data / Tegniese data	BADU®Koi 1	BADU®Koi 2	BADU®Koi 3	BADU®Koi 4
Filter in m ²	0.17	0.21	0.27	0.29
Filter size in inch	16	20	22	28
Filter sand in kg	40	80	120	160
Weight excl. sand	10.49	13.46	16.52	19.06
Average pool size in lit	25 000	57 000	75 000	87 000
Max Flow rate in m ³ /h at 80kPa	6	9.5	12.5	14.5

Turnover rate in liters / Omkeertempo in liter	BADU®Koi 1	BADU®Koi 2	BADU®Koi 3	BADU®Koi 4
4 Hour Turnover	23 350	38 000	50 000	58 000
6 Hour Turnover	35 000	57 000	75 000	87 000
8 Hour Turnover	46 670	76 000	100 000	116 000